



## 2010 Z28

**A-A** 32 1/4" +/- .1875

**Brace** 7 3/4" +/- .125

**String** 56 1/4"

**Cable** 36 7/8"

**Z Cam**  
(Modular)

Cam setting @ Brace from  
.160 hole to inside of limb

**Speed Rating**  
#70 350 grain arrow

**#1 – 30"**

**.925 gap**

**316-320 fps**

**#2 – 29.5"**

**.850 gap**

**311-315 fps**

**#3 – 29"**

**.575 gap**

**307-311 fps**

**#4 – 28.5"**

**.585 gap**

**300-304 fps**

**#5 – 28"**

**.515 gap**

**294-298 fps**

**#6 – 27.5"**

**.485 gap**

**288-292 fps**

**#7 – 27"**

**.475 gap**

**283-287 fps**

**Deduct 5 fps from rating for #60 peak weight**

**Limb Deflection**

**Poundage of Bow**

**Pivots**

90

90

Tall

105

80

Tall

114

70

Tall

135

60

Tall

**Speed Buttons**

**Qty**

**Location**

Custom Elite

2

1<sup>st</sup> one 4" from axle

**Spacers**

.090 on the string side

.035 on the cable side

**Cable Rod**

7 1/2"

**Suppressor Rod with bends** 5 1/2"